

Minisplit Inverter

Serie Charmo Clase D/E

Simplicidad funcional y rendimiento robusto para un confort económico y duradero.

CAPACIDAD

12K BTU/HR - 18K BTU/HR - 24K BTU/HR

RESIDENCIAL - OFICINAS



La serie Gree Charmo Inverter combina un diseño elegante con tecnología inteligente para ofrecer un equilibrio entre rendimiento y ahorro energético. Con una clasificación energética D/E, está diseñada para climas exigentes donde se busca mayor eficiencia que en sistemas tradicionales, pero con una inversión accesible.

Aplicaciones recomendadas:


Habitaciones medianas, salas, oficinas o locales comerciales donde se valora el confort continuo y una eficiencia energética moderada sin sacrificar diseño.



Voltaje **220V**

Refrigerante

R32




Tecnología Inverter: Modula el funcionamiento del compresor para mantener la temperatura estable, reducir el consumo eléctrico y alargar la vida útil del equipo.



Serie Charmo: Estética moderna y acabados sobrios que se integran perfectamente a espacios residenciales y profesionales.




Refrigerante R410A: Buen rendimiento térmico y menor impacto ambiental comparado con gases antiguos.



Clase energética D/E: Más eficiente que los sistemas On/Off estándar, ideal para quienes buscan mejorar el **consumo sin pagar por gamas premium.**



Control remoto y funciones avanzadas: Modo sueño, turbo, temporizador y autodiagnóstico para mayor comodidad y control.



Operación silenciosa: Disfruta de un ambiente fresco sin ruidos molestos.

TABLA DE ESPECIFICACIONES

ITEM	UNIT	DATA	DATA	DATA	DATA
Model	--	GWC12ATBXB-A6DNA1B	GWC12ATBXA-D6DNA1A	GWC18ATDXB-D6DNA1A	GWC24ATDXE-S6DNA1A
Power Supply Mode	V/Ph/Hz	110/1/60	220/1/60	220/1/60	220/1/60
Power Supply Mode	-	Outdoor	Outdoor	Outdoor	Outdoor
Cooling Capacity	kBtu/h	11400	11900	17500	23000
Cooling Power Input	W	1209	1209	1712	2150
Cooling Current Input	A	12	5.21	7.5	8.2
EER	W/W	3	3	3	3
Class		E	E	D	D
Air Flow Volume(SS/H/MH/M/ML/L/SL)	CFM	383/330/265/224/200/188/0	364/294/264/241/217/194/158	618/559/471/441/383/324/294	638/522/464/435/340/310/280
Application Area	m2	16-24	16-24	21-31	23-34
Indoor Unit Model	--	GWC12ATBXB-A6DNA1B/I	GWC12ATBXA-D6DNA1A/I	GWC18ATDXB-D6DNA1A/I	GWC24ATDXE-S6DNA1A/I
Indoor Unit Fan Type	-	Cross-flow	Cross-flow	Cross-flow	Cross-flow
Evaporator Form	-	Aluminum Fin-copper Tube	Aluminum Fin-copper Tube	Aluminum Fin-copper Tube	Aluminum Fin-copper Tube
Fuse Current	A	3.15	3.15	3.15	3.15
Set Temperature Range	℃	16~30	16-30	16~30	16~30
Indoor Unit Dimension (W x H x D)	mm	783/260/185	783/260/185	943/333/246	943/333/246
Indoor Unit Dimension of Packege (W x H x D)	mm	823/316/247	823/316/247	996/397/312	996/397/312
Indoor Unit Net/Gross Weight	kg	7.5/9	7.5/9	13/15.5	13/15.5
Outdoor Unit Model	--	GWC12ATBXB-A6DNA1B/O	GWC12ATBXA-D6DNA1A/O	GWC18ATDXB-D6DNA1A/O	GWC24ATDXE-S6DNA1A/O
Compressor type	--	Inverter rotary	Inverter rotary	Inverter rotary	Inverter rotary
Outdoor Unit Fan Type	-	Axial-flow	Axial-flow	Axial-flow	Axial-flow
Condenser Form	-	Aluminum Fin-copper Tube	Aluminum Fin-copper Tube	Aluminum Fin-copper Tube	Aluminum Fin-copper Tube
Cooling Operation Ambient Temperature Range	℃	18~43	18~43	18~43	18~43
Throttling Method	-	Capillary	Capillary	Capillary	Capillary
Outdoor Unit Dimension (W x H x D)	mm	732/555/330	710/450/293	732/555/330	873/555/376
Outdoor Unit Dimension of Package (W x H x	mm	791/590/373	761/500/327	791/590/373	948/591/428
Outdoor Unit Net Weight	kg	24/26.5	19/21	24/26.5	32.5/35.5
Refrigerant	--	R32	R32	R32	R32
Refrigerant Charge	kg	0.34	0.4	0.65	0.7
Connection Pipe Length	m	5	5	5	5
Connection Pipe Gas Additional Charge	g/m	12	12	12	12
Outer Diameter of Liquid Pipe(Client Allocation)(British System)	inch	1/4"	1/4"	1/4"	1/4"
Outer Diameter of Gas Pipe(Client Allocation)(British System)	inch	3/8"	3/8"	3/8"	1/2"
Max Distance Height	m	10.0	10.0	10.0	10.0
Max Distance Length	m	20	20	25	25